

Surface Mounted Light

PARMIS-SURFACE-MOUNTED

Golnoor

Light up Your Life



Learn more about “Parmis-surface-mounted”

The Parmis surface-mounted light, with its modern design and advanced technical specifications, is ideal for indoor use in educational, healthcare, office, retail, and terminal spaces. Featuring an integrated LED module, a color rendering index of 85, and a luminous efficiency of 106, this light provides a luminous flux of 2550 lumens. It offers easy installation, an impressive lifespan of 70,000 hours, and operates with a power factor of 0.95, reducing harmonic distortion and ensuring high energy efficiency.



Class I



High PF



LED luminaire



Modular




Quick
installation



Symmetrical
light emission

- **Parmis-surface-mounted**



Surface Mounted Light

5 years Golnoor Warranty

- **Index : Nominal Size**

- 300 × 300
- 600 × 600
- 1200 × 300

- **Applications**

- Indoor
- Retail & Commercial
- Offices
- Residential Complexes
- Healthcare
- Corridors, Stairs & Lifts
- Shops & Showrooms
- Schools & Universities
- Hospitals
- Clinics & Medical Offices
- Libraries
- Control & Server Rooms

- **Solutions**

- Architectural Lighting

PARMIS-SURFACE-MOUNTED

TECHNICAL SPECIFICATIONS

Review the technical specifications, dimensions, performance data, and related resources for Parmis-surface-mounted


Index (Nominal Size)	300 × 300	600 × 600	1200 × 300
Optical characteristics			
LED Package Nominal Power (W)	1.5		
Initial SDCM (SDCM)	5		
Color Rendering Index	85		
LED Module Type	Integrated		
Light Source	SMD LED		
Lumen Maintenance Code	9		
LEDs Per Module (pcs)	40	72 120	72 120
Luminous Flux (lm)	2550	5000 7500	5000 7500
Luminaire Efficacy (lm/W)	106	125	125
Color Temperature (K)	4000 6500		
Electrical characteristics			
Input Voltage (V)	Min 180 Max 265		
Input Frequency (Hz)	Min 50 Max 60		
Nominal Input Voltage (V)	230		
Nominal Input Frequency (Hz)	50		
Power Factor	0.95		
Total Harmonic Distortion (%)	15		
Electric Shock Protection Class	I		
Type of Power Supply	Independent		
Power (W)	24	40 60	40 60
Nominal Input Current (A)	0.11	0.186 0.274	0.183 0.274
LED Module Operating Voltage (V)	57	18	18
General characteristics			
Mounting Type	Surface Mounted		
Working Temperature Range (°C)	Min -45 Max 55		
Maximum Relative Humidity (%)	90		
Rated Useful Life L70B10 (h)	70000		
Warranty (year)	5		
Mechanical characteristics			
Housing Material	Polymer		
Optical Cover Material	PS		
Ingress Protection	IP42		
Dimensions (mm)	L: 300 · W: 300 · H: 51	L: 600 · W: 600 · H: 51	L: 1200 · W: 300 · H: 51
Weight (kg)	1.1	3.71	4.35

L: length · W: width · H: height · Ø: diameter

This is a compact product summary; visit the website for more details.
<https://golnoor.com/en/product/parmis-surface-mounted>

Models

This product is offered in multiple configurations and models to suit a wide range of project requirements.



01 | Nominal Size: {"length":300,"width":300}



02 | Nominal Size: {"length":600,"width":600}



03 | Nominal Size: {"length":1200,"width":300}

Golnoor

Light up Your Life

WWW.GOLNOOR.COM
