



Pendant Light | Linear Light

PROXIMA 4 PENDANT

Golnoor

Light up Your Life

Learn more about “Proxima 4 pendant”

Proxima 4 Pendant features a slim-profile linear design developed to create seamless lighting systems for indoor spaces. Its suspended installation allows the luminaire to serve not only as a lighting solution but also as a distinctive architectural element, making it particularly suitable for spaces with high ceilings or projects where lighting plays a key role in the visual identity of the interior. The luminaire supports continuous linear runs as well as a variety of layouts, including corners, intersections, and custom configurations, allowing lighting to integrate naturally with the architecture. This flexibility makes Proxima 4 Pendant suitable for offices, commercial buildings, educational facilities, healthcare environments, hotels, retail spaces, and other interior applications.



Class I



Continuous Mounted



High PF



LED luminaire



Loop Through



Modular



Suspended luminaire



Symmetrical light emission

● Proxima 4 pendant



Pendant Light | Linear Light

5 years Golnoor Warranty

● Index : Length (Millimetre)

- 570
- 850
- 1130
- 1690
- 2250
- 3370

● Applications

- Indoor
- Retail & Commercial
- Offices
- Residential Complexes
- Healthcare
- Meeting & Conference Rooms
- Lobbies & Receptions
- Restaurants & Cafés
- Hotels
- Shops & Showrooms
- Libraries
- Exhibition Halls
- Airports & Stations

● Solutions

- Architectural Lighting

PROXIMA 4 PENDANT

TECHNICAL SPECIFICATIONS

Review the technical specifications, dimensions, performance data, and related resources for Proxima 4 pendant

Index (Length (Millimetre))	570	850	1130	1690	2250	3370
Optical characteristics						
Initial SDCM (SDCM)	5					
Color Rendering Index	75					
LED Module Type	Integrated					
Light Source	SMD LED					
Lumen Maintenance Code	9					
Luminous Flux (lm)	780 ~ 1,800 780 · 820 · 1700 · 1800	1,340 ~ 2,850 1340 · 1410 · 2700 · 2850	1,730 ~ 3,800 1730 · 1820 · 3600 · 3800	2,600 ~ 5,670 2600 · 2760 · 5387 · 5670	3,450 ~ 7,570 3450 · 3630 · 7190 · 7570	5,160 ~ 11,370 5160 · 5430 · 10800 · 11370
Color Temperature (K)	3,000 ~ 6,500 3000 · 4000 · 5000 · 6500					
LEDs Per Module (pcs)	40 ~ 200 40 · 60 · 80 · 120 · 160 · 200					
Luminaire Efficacy (lm/W)	78 ~ 95 78 · 82 · 85 · 86 · 87 · 89 · 90 · 91 · 92 · 94 · 95					
Electrical characteristics						
Input Voltage (V)	Min 180 Max 265					
Input Frequency (Hz)	Min 50 Max 60					
Nominal Input Voltage (V)	230					
Nominal Input Frequency (Hz)	50					
Power Factor	0.95					
Total Harmonic Distortion (%)	15					
Electric Shock Protection Class	I					
Type of Power Supply	Independent					
Power (W)	10 20	15 30	20 40	30 60	40 80	60 120
Nominal Input Current (A)	0.046 ~ 0.55 0.046 · 0.07 · 0.09 · 0.14 · 0.18 · 0.275 · 0.366 · 0.55					
LED Module Operating Voltage (V)	30 ~ 360 30 · 45 · 60 · 90 · 120 · 180 · 240 · 360					
General characteristics						
Mounting Type	Pendant Mounted					
Working Temperature Range (°C)	Min -45 Max 55					
Maximum Relative Humidity (%)	90					
Rated Useful Life L70B10 (h)	70000					
Warranty (year)	5					
Mechanical characteristics						
Housing Material	Aluminium					
Optical Cover Material	PMMA					
Surface Finish	Electrostatic Powder Coating					
Ingress Protection	IP42					
Dimensions (mm)	L: 570 · W: 40 · H: 76	L: 850 · W: 40 · H: 76	L: 1130 · W: 40 · H: 76	L: 1690 · W: 40 · H: 76	L: 2250 · W: 40 · H: 76	L: 3370 · W: 40 · H: 76
Weight (kg)	1.16 ~ 5.15 1.16 · 1.56 · 1.93 · 2.73 · 3.51 · 5.15					


L: length · W: width · H: height · Ø: diameter

This is a compact product summary; visit the website for more details.

<https://golnoor.com/en/product/proxima-4-pendant>

Dimensions

Review overall dimensions and layout drawings for installation planning, placement, and site coordination.



01 | Proxima 4 pendant

Golnoor

Light up Your Life

WWW.GOLNOOR.COM
