



Street Light

SETAREH-XL

Discontinued

Golnoor

Light up Your Life



Learn more about “Setareh-XL”

The Setareh XL street light is a product with the right power and size for lighting urban streets. It is available in three models with 250, 300, or 340 watts of power and can be used for a variety of applications with its wide range of color temperatures. The Setareh XL street light has an advanced cooling system that increases its lifespan.



Asymmetrical



Class I



Full cut-off



High PF



IP66



LED luminaire



Modular



Quick installation



Street Lighting

● Setareh-XL



Street Light

5 years Golnoor Warranty

● Index : Power (watt)

— 250

— 300

— 340

● Applications

— Outdoor

— Streets & Roads

● Solutions

— Road & Highway Lighting

SETAREH-XL

TECHNICAL SPECIFICATIONS

Review the technical specifications, dimensions, performance data, and related resources for Setareh-XL

Index (Power (watt))	250	300	340
Optical characteristics			
LED Package Nominal Power (W)	1.5		
Initial SDCM (SDCM)	5		
Color Rendering Index	75		
LED Module Type	Integrated		
Light Source	SMD LED		
Lumen Maintenance Code	9		
LEDs Per Module (pcs)	432	480	576
Luminous Flux (lm)	35600 37500	42700 45000	48400 51000
Luminaire Efficacy (lm/W)	142 150		
Color Temperature (K)	3,000 ~ 6,500 3000 · 4000 · 5000 · 6500		
Electrical characteristics			
Input Voltage (V)	Min 180 Max 265		
Input Frequency (Hz)	Min 50 Max 60		
Nominal Input Voltage (V)	230		
Nominal Input Frequency (Hz)	50		
Power Factor	0.95		
Total Harmonic Distortion (%)	15		
Electric Shock Protection Class	I		
LED Module Operating Voltage (V)	36		
Type of Power Supply	Independent		
Nominal Input Current (A)	1.14	1.37	1.55
General characteristics			
Mounting Type	Pole Mounted		
Working Temperature Range (°C)	Min -45 Max 55		
Maximum Relative Humidity (%)	95		
Rated Useful Life L70B10 (h)	100000		
Warranty (year)	5		
Mechanical characteristics			
Housing Material	Die-Cast Aluminum		
Optical Cover Material	Tempered Glass		
RAL Colour	Graphite Grey (RAL 7024)		
Surface Finish	Electrostatic Powder Coating		
Surface Texture	Sanded		
Dimensions (mm)	L: 736 · W: 390 · H: 141		
Weight (kg)	12.3		
Spigot Diameter (mm)	60		
Default Spigot Diameter (mm)	60		
Ingress Protection	IP66		
Body Impact Protection	IK09		
Diffuser Impact Protection	IK07		

L: length · W: width · H: height · Ø: diameter

This is a compact product summary; visit the website for more details.

<https://golnoor.com/en/product/setareh-xl>

Models

This product is offered in multiple configurations and models to suit a wide range of project requirements.



01 | Power: 250



02 | Power: 300



03 | Power: 340

Golnoor

Light up Your Life

WWW.GOLNOOR.COM
